

FloorTac™

Print Media

FloorTac™ is a 3.2 mil (80µ) printable matte white polymeric PVC film with a removable, pressure sensitive gray acrylic adhesive protected by a poly coated Kraft release liner. It is recommended for use with Drytac's Emerytex® laminating films to provide slip resistance.

Typical Applications

- Ideal for short-term indoor advertising where graphics are applied to floor or ceramic tiles, sealed wood or concrete, waxed vinyl, marble, or terrazzo.
- Ideal for use in schools, hospitals, supermarkets, and restaurants.
- Suitable for medium foot traffic areas.
- Use in combination with Drytac's Emerytex® laminating films for an approved slip-resistant finish.
- For best results, leave a 0.25" (6mm) non-printed border around the edge of the image.

Print Compatibility

- (Eco) Solvent
- Latex
- UV

Product Structure

Film	Matte White Polymeric PVC	4.2 mil (105µ)
Adhesive	Acrylic (Pressure Sensitive)	
Release Liner	90# Poly Coated Kraft	

Physical Characteristics

Film Thickness	3.2 mil (80µ)
Adhesive Layer	1 mil (25µ)
Film/Adhesive Ratio	3.2:1
UV Protection Factor	Not Applicable
Outdoor Durability	Not Applicable
Application Temperature	>-4°F (-20°C)
Service Temperature Range	-22°F to 302°F (-30°C to 150°C)
Shelf Life	Use within 1 year after opening original box
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

Overlamine Recommendations

When using FloorTac™, an overlamine can be used for maximum life expectancy. Products recommended for use with FloorTac™ are Drytac's Emerytex® overlaminates.

Installation Recommendations

Please see FloorTac™ installation instructions for further details. The surface must be clean and smooth and free of defects before application.

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.