INTERLAM™ OVERLAMINATES

Interlam[™] clear overlaminates are pressure sensitive films, comprised of Drytac's Eco and Pro lines.

The Interlam[™] Eco line consists of PP films with an aqueous acrylic adhesive that provide image enhancement and moisture protection for indoor graphics.

The Interlam™ Pro line includes PVC base films with an acrylic adhesive as well as UV stabilizers and absorbers for added protection. Their high adhesive coat weight is ideal for UV, latex and solvent printed material.



- Can be applied quickly and easily
- Interlam™ EcoGloss™ is internationally approved for direct food contact
- Interlam™ Pro Emerytex® provides a slip-resistant finish for floor graphics
- Interlam™ Pro overlaminates have excellent resistance to UV light, weather and temperature changes and are outdoor durable for 3 years



DURABLE

What to Laminate

- Digital prints and photographs
- Wallcoverings and self-adhesive vinyl
- POP displays and promotional graphics
- Architectural renderings and maps
- Tradeshow graphics and event signage
- Mouse pads, placemats or counter graphics

Where to Use

High traffic indoor display areas where:

- Specific lighting conditions cannot be controlled
- Graphics will be viewed under direct lighting from different angles
- Graphics may be subject to extensive handling

Outdoor applications, including construction barricades or places where graffiti might be a possibility, such as bus shelters, train stations and kiosks



Product	Mil	Film	Finish
EcoGloss™	2.5 (1.5/1)	PP	Gloss
EcoTex™	6.5 (5.5/1)	PP	Pebble texture
Pro Glossy	4 (3/1)	PVC	Gloss
Pro Lustre	4 (3/1)	PVC	Lustre
Pro Matte	4 (3/1)	PVC	Matte
Pro Emerytex®	5 (4/1)	PVC	Pebble texture
Pro Anti-Graffiti	2 (1/1)	PCTFE	Gloss anti-graffiti

