

MHL™ Frost™

Overlaminating Film

MHL™ Frost™ is a 6 mil (152µ) embossed composite thermal laminating film with a crystal textured finish that offers a scratch-resistant, non-reflective surface for graphic enhancement. The finish minimizes reflectivity of bright light surroundings while allowing brilliant colors to shine through. MHL™ Frost™ incorporates ultra low melt-point technology in a textured laminating film. The film is resistant to water, oil, acid, alkali, and fingerprints. It is very durable and can be die-cut.

Typical Applications

- Recommended for display applications, especially exhibition and POS graphics.
- Ideal for pop-up display panels and roll-up banners.
- Performs well in high-traffic areas.

Physical Characteristics

Film Thickness	6 mil (152µ)
Film/Adhesive Ratio	3:3
Processing Temperature	185°F to 195°F (85°C to 91°C)
Shelf Life	Use within 1 year after opening original box
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.