

MHL™ Scribe™

Overlaminating Film

MHL™ Scribe™ is a 3 mil (75µ) high clarity, abrasion-resistant PP thermal laminating film with a gloss finish. The film is engineered with a specially formulated copolymer thermal adhesive for a low melt-point for single-sided lamination. With its dry erase characteristics, black dry erase markers can be wiped clean with a dry cloth.

Typical Applications

- Ideal for laminating book jackets, report covers and other specialty applications.
- Suitable for courtroom displays.
- Can be used for short-term dry erase boards.

Physical Characteristics

Film Thickness	3 mil (75µ)
Film/Adhesive Ratio	0.5:2.5
Processing Temperature	210°F to 230°F (99°C to 110°C)
Shelf Life	Use within 1 year after opening original box
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.