Technical Data Sheet

MHL[™] Soft Velvet Touch

Overlaminating Film

MHL[™] Soft Velvet Touch is a 1.4 mil (35µ) nylon thermal laminating film with a velvet matte finish and anti-curl properties. It provides excellent clarity and a soft, luxurious feel to graphics. The film also offers scuff resistance for added protection.

Typical Applications

- Recommended for soft book covers, postcards, pocket folders, brochures, calendars, and presentation covers.
- Ideal for single-sided lamination.

Physical Characteristics

Film Thickness	1.4 mil (35µ)
Film/Adhesive Ratio	0.7:0.7
Processing Temperature	240°F to 260°F (115°C to 127°C)
Shelf Life	Use within 1 year after opening original box
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.

Ι