

# MHL™ Standard Temperature Gloss

*Overlaminating Film*

MHL™ Standard Temperature Gloss is a 1.7 mil (43μ) high clarity, abrasion-resistant PET thermal laminating film designed for high-speed single- or double-sided lamination. The film is resistant to water, oil, acid, and alkali and can be die cut.

## Typical Applications

- Ideal for laminating book jackets, posters, menus, and maps.
- Recommended for applications that require excellent clarity and protection.

## Physical Characteristics

<i>Film Thickness</i>	1.7 mil (43μ)
<i>Film/Adhesive Ratio</i>	0.5:1.2
<i>Processing Temperature</i>	210°F to 230°F (99°C to 110°C)
<i>Shelf Life</i>	Use within 1 year after opening original box
<i>Storage Conditions</i>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

## IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.