

Printable Eclipse™ Matte

Print Media

Printable Eclipse™ Matte is a 7.5 mil (190µ) fast-drying PET film with a white matte surface that delivers vibrant image quality. This light-blocking print media offers excellent lay-flat, curl-resistant properties and is dimensionally stable. Compatible with aqueous printers, Printable Eclipse™ Matte provides superior ink adhesion. It may be used with both dye and pigment inks to produce images for short-term indoor displays. Recommended for use with Interlam™ Pro Emerytex® for added durability to withstand handling, rolling and shipping. When laminated, the result is a durable graphic that hangs straight and flat without edge fray.

Typical Applications

- Ideal for retractable banner stands or pop-up displays.
- Perfect for frame-supported graphics and trade show/event graphics.
- An excellent choice for interior retail graphics.
- Great for seasonal retail graphics.
- Recommended for applications where a blackout or semi-rigid film is required.

Print Compatibility

- Aqueous

Product Structure

Ink Receptive Top Coat	1 mil (25µ)	7.5 mil (190µ)
Film	PET	
Blockout Layer	Silver Back	

Physical Characteristics

Film Thickness	7.5 mil (190µ)
Finish	Matte
UV Protection Factor	Not Applicable
Outdoor Durability	Short-Term
Service Temperature Range	-4°F to 146°F (-20°C to 63°C)
Shelf Life	Use within 1 year after opening original box
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.