

ViziCling™ White

Print Media

ViziCling™ White is an 8 mil (203µ) flexible, white opaque static cling PVC film with a PE coated Kraft release liner for exceptional clarity. No adhesive is required. It can be easily applied to and quickly removed from most smooth, flat surfaces. The film is very durable and offers excellent chemical resistance and adhesion. The non-printed side of the vinyl adheres securely to glass and other highly polished surfaces.

Typical Applications

- Ideal for applications on glass and other smooth, flat surfaces.
- Can be used for window graphics, decals, labels, and stickers.
- Suitable for indoor and outdoor window applications.

Print Compatibility

- (Eco) Solvent
- Latex
- UV

Product Structure

Film	White Opaque Flexible PVC	19 mil (482µ)
Adhesive	None	
Release Liner	PE Coated Kraft	

Physical Characteristics

Film Thickness	8 mil (203µ)
Release Liner Layer	11 mil (279µ)
Film/Release Liner Ratio	8:11
UV Protection Factor	Not Applicable
Outdoor Durability	2 years (interior of glass)
Application Temperature	>40°F (4°C)
Service Temperature Range	-10°F to 150°F (-23°C to 65°C)
Shelf Life	Use within 6 months after opening original box
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

Installation Recommendations

Wet or dry installation can be used for ViziCling™ White. The surface must be clean and smooth and free of defects before application.

Printing Recommendations

- Handle material with care prior to printing; use gloves to avoid fingerprints.
- Roll graphics with the release liner on the outside of the roll to prevent the release liner from tunneling.

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.