



# VISUAL MAGNETICS GRAPHIC SYSTEM®

## VM-POLYeight® UV

Visual Magnetics® VM-POLYeight UV is a 12-mil\*, magnetic receptive white polyester film with a high gloss print surface. VM-POLYeight UV is ideal for producing high resolution photo and artwork reproductions, overlays, and economical POP signage using most digital and analog printing technologies and features a patented Micro-Iron® back-coating enabling displays to be effortlessly updated, easily installed, layered, transported, stored or recycled.

Roll-Out



### Features and Benefits

- Premium gloss print coating optimized for analog and UV-Cured print devices.
- 12-mil\* polyester base. Economical with quality “hand.”
- Water / smudge resistant print surface.
- 100% opaque – No show through.
- Easy to install – No frames, wraps or stretching necessary.
- PVC free.

### Application Information

- Excellent for durable displays and POP signage.
- Apply, remove and store like any other MagnaMedia.
- Polyester base designed for high temperature applications.

### Physical Data

<b>Total Caliper*</b>	12-mil / 305 Micron	<b>Opacity</b>	100%
<b>Gloss</b>	Gloss	<b>Fire Rating</b>	Class A (ASTME-84-98)
<b>Whiteness*</b>	100%	<b>Optimal Conditions</b>	50% RH / 70°F

### Products / Sizes

PRODUCT CODE	AVAILABLE SIZES	
VMP8UV-54100	54 in x 100 ft – 3 in core	(137.2 cm x 30.5 m)
VMP8UV-60100	60 in x 100 ft – 3 in core	(152.4 cm x 30.5 m)

\* Thickness and whiteness listed is nominal.

MagnaMedia® POLYESTER FILMS

# VM-POLYeight® UV (Continued)

## Printer Compatibility

**VM-POLYeight UV** is compatible with most UV-Cured and analog printing technologies (see chart).



## Recyclability

All MagnaMedia, including **VM-POLYeight UV**, will be recycled into energy and new steel production when returned to Visual Magnetics per our "Recycling Retired Graphics" program available for download at [www.visualmagnetics.com](http://www.visualmagnetics.com).

## Protecting Images

Liquid laminates are recommended as they can be easily applied to the textured surface with good results. Apply minimally to maintain surface texture. Always pretest liquid laminates for compatibility prior to applying to finished graphic.

Renew



The information presented in this product data sheet is based upon Visual Magnetics' present knowledge of the product and is believed to be accurate. Products often are improved which may cause the current information presented to be out of date. It is always the users responsibility to determine suitability of this product for the intended application prior to production.