

ViziPrint® Deco

Print Media

ViziPrint® Deco is a 2 mil (50μ) optically clear gloss PET film, coated with a permanent clear acrylic adhesive and protected by a siliconized PET release liner that has a super smooth profile to enhance the clarity when applied to glass. It has a special top coat to enhance the adhesion of inks. The film's high quality adhesive adheres to most substrates.

Typical Applications

- Ideal for high quality graphics for retail storefronts, POP and backlit displays, and window labels and decals.
- Suitable for conference rooms and architectural applications.

Print Compatibility

- Latex
- UV

Installation Recommendations

The surface must be clean and smooth and free of defects before application. Use gloves to avoid fingerprints. Wet installation is recommended.

Product Structure

Film	Gloss Transparent PET with Ink-Receptive Top Coat	2.8 mil (70μ)
Adhesive	Clear Permanent Acrylic (Pressure Sensitive)	
Release Liner	0.5 mil Siliconized PET	

Physical Characteristics

Film Thickness	2 mil (50μ)
Adhesive Layer	0.8 mil (20μ)
Film/Adhesive Ratio	2:0.8
UV Protection Factor	Not Applicable
Outdoor Durability	2 years
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 266°F (-20°C to 130°C)
Shelf Life	Use within 1 year after opening original box
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein. Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.